

### Safety Statement

- The demonstrations performed today involve chemicals in active chemical reactions. They have all been developed, tested and published by professionals in the Chemistry Education Field. We have performed them repeatedly without incident though we want to mention that outcomes can be unpredictable.
- If you have pre-existing respiratory conditions, known allergic reactions to chemicals, are sensitive to loud noises, or if you are simply concerned, you may consider sitting near the rear of the classroom, closer to the outdoor ventilation
- This seminar is offered as information only. No warranty, representation, or guarantee is made by the instructors as to the accuracy or sufficiency of the information offered during this seminar. Any references to laws and regulations must be verified in appropriate legal reference sources before use out in the field.
- Do not attempt any of these demonstrations on your own based on information gathered during this seminar. There must be extensive education, research, testing, and practice done before attempting to perform any of these demonstrations.
- Per Proposition 65, note that some of the flammable and combustible liquids used today are known by the State of California to cause cancer, birth defects or other reproductive harm.



### FUN WITH CHEMISTRY







### Dan Keenan Maria Duazo








"Good judgement proceeds from clear understanding, clear understanding comes reason derived from sound rules, and sound rules are daughters of















# Cryogenics


• Liquefied Refrigerated gases with boiling points less than -130°F

Helium -452°F Nitrogen
321°F

Oxygen -291°F Hydrogen -423°F







# Cryogenics

• Liquefied Refrigerated gases with boiling points less than -130°F

Helium -452°F

321°F


*Oxygen* -291°F 423°F Nitrogen

Hydrogen



- **×** Surface Area
  - extremely important to consider
  - very finely divided particles
  - sawdust, grain dust, flour, coal dust
  - not regulated by DOT Copyright © DanKeenan & Mari









- Chemical Reaction
  - result in a new substand
  - are not easily reversible


• Chemical reactions involve a change in






- 3 types:
  - Combination
  - Decomposition
  - Displacement
    - single replacement
    - double replacement








$$2H_2 + O_2 \wedge 2H_2O$$



- - carcinogen, teratogen, asphyxiant, sensitizer
  - neurotoxin, hemotoxin, nephrotoxin
- Hazardous to Environment
  - gases, particulates
  - oxygen demanding, plant nutrients, bioaccumulative
  - municipal solid waste, hazardous waste
- Hazardous to Property
  - NFPA 704 system, DOT hazard classes



#### Miscellaneous Hazardous Materials

- Class 9
  - -elevated temperature materials
  - -hazardous substances
  - -marine pollutants
  - -hazardous waste
    - asbestos, castor beans, cotton, sulfur
    - iodine hazardous waste solid, n.o.s.

### Consumer Commodities

 Materials that are packaged in a form intended for sale through retail agencies for consumption by individuals



 The flammability of aerosols is determined by the criteria in 49 CFR 173.306 as, "using B.O.E.'s Flame Projection Apparatus, the flame projects greater than 18" beyond the ignition source"





• Definition:

- A *corrosive* material means:

- "a liquid or solid that causes full thickness destruction of human skin at the site of contact."

"a liquid that has a severe corrosion rate on steel or aluminum."










*− Packing Groups 1, 2 & 3.....* 


causes full thickness destruction of skin tissue within an observation period of:


1 hour after an exposure of 3 minutes or less

14 days after an exposure of 3° to Date of 3










Place one (prepared and refrigerated)
Biobarrier Disc in the top of each vial.
Begin test immediately (no later than 2 minutes).


- Add 500 µl (liquid) or 500 mg (solid) of your test sample and control chemicals into Biobarrier Discs in each of the 6 vials and start timers. Caution: Do not cap the vials during the test due to possible pressure build up.
- As soon as a reaction is observed in the Chemical Detection System, record the detection time.


Remove each Biobarrier Disc, cap and dispose of vials using your lab protocol for proper chemical disposal.






**2H<sub>2</sub>O** 







#### Is it Hazardous Waste?

• A solid waste exhibits the characteristic of corrosivity if a representative sample of the waste is:

Aqueous, with a pH
 less than or equal to 2.0,
 or greater than or equal to 12.5




a value that represents the acidity or alkalinity of an aqueous solution.



• Now, WHAT did you say?...



- How do we buy buy eggs?
  - By the dozen



- How do we buy rice?
  - By the pound



- Mole:
  - a convenient way of measuring atoms
  - equals Avogadro's # of molecules or atoms
  - equals molecular weight or atomic weight
    - expressed in grams



- **>** logarithmic
- > intervals are exponential
- each unit is equivalent to a ten-fold difference from the unit before it
- > a pH 1 is how many times more acidic than a pH 3?, a 4?

рН	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
H <sup>+</sup> ions	10 <sup>0</sup>	10 <sup>-1</sup>	10 <sup>-2</sup>	10 <sup>-3</sup>	10 <sup>-4</sup>	10 <sup>-5</sup>	10 <sup>-6</sup>	10 <sup>-7</sup>	10 <sup>-8</sup>	10 <sup>-9</sup>	10 <sup>-10</sup>	10 <sup>-11</sup>	10 <sup>-12</sup>	10 <sup>-13</sup>	10 <sup>-14</sup>	



- pH paper is the most common
- Indicator Solutions
- pH meter





	Fluid	pН	Fluid	рH
•	Stomach Acid	1.5	Milk	6.5
•	Lemon Juice	2.4	Pure water	7.0
•	Vinegar	3.0	Blood	7.4
•	Orange Juice	3.5	Bile	8.3
•	Urine	6.0	Milk of Magnesia	10.6
•	Saliva	6.7	Ammonia	11.5



any material having a *specific* activity > .002 microcurie/gram

activity = # of disintegrations per









 Atoms of the same element containing a different number of *neutrons* in the nucleus




Table of Radioactive Isotopes (Continued)

Element	A	Half-life	Radiation (MeV)			
	229	7340y	α(4.90, 4.84, 4.81), Ra-x, γ(0.137, 0.20)			
	*230(Io)	$7.54 \times 10^{4}$ y	$\alpha(4.68, 4.62), Ra-x, \gamma(0.068)$			
	*231(UY)	1.0633d	$\beta$ =(0.302, 0.218, 0.138), Pa-x, $\gamma$ (0.026, 0.084)			
	*232(Th)	$1.405 \times 10^{10}$ y	$\alpha(4.01, 3.95), \gamma(0.059)$			
	*234(UX <sub>1</sub> )	24.10d	β (0.199, 0.104), Pa-x, γ(0.029, 0.063, 0.092, 0.093, 0.113)			
Protactinium	228	22h	K, α(6.11, 6.08, 6.03, 5.80), Th-x, γ(0.410, 0.463, 0.965, 0.969)			
	229	1.4d	K, α(5.67, 5.62, 5.58, 5.54), Th-x			
	230	17.4d	K, $\beta^{-}(0.509)$ , $\alpha(5.34, 5.33, 5.31, 5.30)$ , Th-x, $\gamma(0.444, 0.455, 0.899, 0.919, 0.952)$			
	*231(Pa)	$3.276 \times 10^4 y$	α(5.06, 5.02, 5.01, 4.95, 4.73), Ac-x, γ(0.027, 0.284, 0.300, 0.303)			
	232	1.31d	$\beta$ (0.32, 1.19, 1.30), U-x, $\gamma$ (0.150, 0.894, 0.969)			
	233	27.0d	β-(0.257, 0.15, 0.568), U-x, γ(0.312)			
	*234m(UX <sub>2</sub> )	1.17min	β-(2.29), IT, U-x, γ(0.765, 1.00)			
	*234(UZ) "	6.70h	β-(0.68, 0.51, 0.28), U-x, γ(0.131, 0.570)			
Neptunium	231	48.8min	K, $\alpha$ (6.28), $\gamma$ (0.264, 0.348, 0.371), no $\beta$ <sup>+</sup>			
	233	36.2min	K, α(5.54), U-x, γ(0.299, 0.312)			
	234	4.4d	K, β+(0.8), U-x, γ(1.528, 1.559, 1.602)			
	235	1.085y	K, a(5.02), U-x, y(0.026, 0.084)			
			K, β-(0.537), U-x, γ(0.045, 0.643, 0.688)			
<b>V</b>	236	22.5h				
	236	$1.550 \times 10^{5} \text{y}$	Κ, β-, γ(0.160)			
4/	237	$2.140 \times 10^{6}$ y	α(4.79, 4.77), Pa-x, γ(0.029, 0.086)			
	238	2.117d	β-(1.24, 0.28, 0.25), γ(0.984, 1.026, 1.029)			
	239	2.355d	β-(0.437, 0.332, 0.393, 0.713), Pu-x, γ(0.106, 0.228, 0.278)			
	240m	7.22min	$\beta$ -(2.18, 1.60, 1.30), $\gamma$ (0.555, 0.597)			
	010111 000	Control of the Contro	$\beta^-(0.89)$ , $\gamma(0.448, 0.566, 0.974)$			
	2411	1.0020	n w.ozi. xw.440. v.200, v.zi4)			
	240 241	1,032h 13.9min	$\beta^{-}(1.4)$ , $\gamma(0.135, 0.175)$ , no $\alpha$			




Approach a spill using

- -Time
- Distance
  - inverse square law
- Shielding
- and the "ALARA principle"



### Radioactive - Yellow II



### Poisons - Class

Materials,
other than gases,



humans that they afford a hazard to health during

known to be so toxic to

transportation.....



Presumed to be Toxic to Humans

**Acute Toxicity (Testing on Lab Animals)** 

Oral LD50 for liquids < 500 mg/Kg

for solids < 200 mg/kg

Acute dermal LD50 < 1,000 mg/Kg

Acute inhalation LC50 < 10 mg/L

as a dust or mist





### OXICIZE ORGANIC PEROXIDE S.2



- An oxidizer as defined in 49CFR,

  "a material that may,
  generally by yielding oxygen,
  cause or enhance the
  combustion of other materials."
- Oxidizers as a class, are reactive and support combustion through the release of oxygen, heat or both.




Let's take a look at some oxidizers!!!!



- **☑ Oxygen**
- **Oxy-Salts**
- Malogens
- **✓** Oxy-Acids
  - **Nitric acid**
  - **Order** Chromic acid
  - **Perchloric acid**
- **✓** Metal Peroxide Salts







- **☑ Oxygen**
- **Oxy-Salts**
- **Halogens**
- **✓** Oxy-Acids
  - **Nitric acid**
  - **Order** Chromic acid
  - Perchloric acid
- **✓** Metal Peroxide Salts






## Organic


## Peroxides Mainly used as initiators and

Mainly used as initiators and catalysts for plastics manufacturing.

 Their explosive nature and their character as unstable fuels are more serious than their hazards as oxidizers.

Some are normally unstable and can undergo violent change;





### A Recognition Clue

• If the compound name has;

















Treat it as an oxidizer!!

# \*Flammable Solids\*\*

**×**DOT Definitions

three divisions:



4.1 Flammable Solid



4.3 Dangerous When Wet Material





either wetted explosives,
thermally unstable self reactive
materials, solids that may cause
fire through friction, or solids that
burn vigorously
above a certain rate of burn.

Let's look at some properties of flammable solids!!!



× Flammable Metals

- \* **Magnesium** ribbons

- × Aluminum
- powder

× Cerium

- ingots
- × Zirconium
- sheets





### **× Flammable Non-Metals**

- \* sulfur
  - ingredient in black powder
  - SO<sub>2</sub> is product of combustion
- **x** (phosphorous
  - 3 allotropes white, red, or black
  - white pyrophoric, stored under water

### spontaneously Combustible

### Pyrophoric

**Materials** 

ignite spontaneously within
 5 minutes after coming in
 contact with air




Diethyl Zinc, White Phosphorous,
 Potassium Sulfide, Pentaborane Copyright Dankeenan & Maria Duazo 1999


# Dangerous when Wet


A material that, by contact with water,
 is liable to become spontaneously flammable
 or to give off flammable or toxic gas

reacts violently with water

- forms potentially explosive mixtures with water









# flammable liquids

Flammable Liquid - flashpoint < 141°F


Combustible Liquid - flashpoint > 141°F




Let's look at some properties of flammable & combustible liquids!!!




gasoline vapors are too lean to burn



Below Flash Point (liquid at -50'F)







### 1. Viscosity

Viscosity is a function of one of 6 things.

- Carbon chain length (separates from water with a distinct line):
  - 1 to 10 carbons viscosity 1
  - 11 to 18 carbons viscosity 2
  - 20 to 25 carbons viscosity 3
  - 29 carbons viscosity 4


One functional group on a long-chain organic will change the viscosity, causing the liquid to become more viscous.

- Multiple functional groups (dissolve in water):
   The greater the number of functional groups,
   the more viscous the material.
- The material is partly polymerized (Curdles or becomes stringy in water)
- The material is a gel (remains unchanged in water, may appear to disappear or hang in water, neither floating nor sinking).
- A solid or viscous liquid is dissolved in liquid (Separates into various components in water)
- 6. Glasses, usually silicates, NOT organic.

### 2. Smoke Colors




### 3. Flame Colors



Hazardous waste with a Flash Point below 140 F is condidered to be Ignitable. There are two main methods for determining flash point Open and Closed cup. The method below is not exact enough to establish a legal classification of Flammable and/or Combustible, but it will give you a field estimation of how flammable the material is. These estimates are given for interpreting the HazCat charts only.

Place a puddle the size of a 50cent piece on the watch dish. Slowly move a lit match (starting from 2 inches away) towards the watch dish, keeping it level with the dish. If the liquid bursts into flame before the match reaches the edge of the watch dish, or as it reaches the dish (this test will be influenced by temperature and air movement), the flash point is below 20 F. Extremely Flammable




If, as you barely touch the puddle of liquid on the watch dish, it bursts into flame, the flash point is below 50 F. To be certain that you are erring on the sale side, consider as Extremely Flammable.



If you touch the puddle, and the liquid ignites fairly quickly, the flash point is below 60 F. Flammable



If the material first soaks into the match, where it quickly wicks, and then steadily covers the total surface area of the liquid with flame, the flash point is below 70 F. Flammable




If the material flashes slightly, wicks and then the flame spreads over the whole surface of the puddle reluctantly, the flash point is below 90 F. Flammable



Warning: Consider any flashing of the liquid, sustained or not, as an indicator that the liquid has a flash point under 100 F.

If the material wicks slowly and steadily, but the flame will not spread over the surface of the liquid, the flash point is above115 F. Combustible for HazCat, but for safety - Treat as Flammable





## What About Empty Containers?

• Adopted CA standards require generator to empty all the material possible from the container.

### Container Management

- Larger than five gallons
  - within 1 year reclaim scrap value or recondition
- Five gallons or less
  - disposed at appropriate facility, reclaim scrap value or recondition
- Household containers
  - only exempt if empty of all contents



The moral of the story is...

- "Empty" containers will contain some residual hazardous materials which could cause significant harm if mismanaged.
- The contaminated container regulations do not classify the containers as non-hazardous at any stage, they only grant an exemption.
   NEVER assume a container is non-hazardous.

## Compressed Gases - Class 2




## flammable gas

An ignitable compressed gas; which is

- a) ignitable when in a mixture of13% or less by volume in air...
- b) has a flammable range of at least 12%...

Let's look at some properties of ignitable gases!!!









H - Hydrogen

A - Acetylene

H - Helium


A - Ammonia

M - Methane

I - Illuminating Gases

C - Carbon Monoxide

E - Ethylene



# 

1 C<sub>3</sub>H<sub>8</sub> +

5\_\_\_\_\_

3

**—** 

4

### EXPLOSIVES

- Division 1.1 mass explosion hazard (TNT)
- Division 1.2 projection hazard but not mass explosion hazard (flares, det. cord)
- Division 1.3 fire hazard and either minor blast or minor projection hazard (liquid-fueled rocket motors)

**1.1** 

• Three other less sensitive types.



 A substance that is designed to function by explosion, or one which by chemical reaction within itself is able to function by explosion

### Low Explosives

• Function by deflagration



- Deflagration
  - low reaction rate, slower than the speed of sound
  - very rapid autocombustion from the surface inward
  - initiation by contact of a spark or flame, but may be by impact or friction
  - examples: black powder, smokeless powder





Most common agent is a fuel-oxidizer system:

ammonium nitrate and fuel oil a.k.a. ANFO.

 Not considered a high explosive, but can detonate under fire conditions.

### High Explosives

Function by detonation



- Detonation
  - high reaction rate faster than the speed of sound
  - almost instant decomposition of a high explosive
  - may be initiated by mechanical impact, friction or heat
  - accompanied by high pressure and temperature waves

